



BIAS CONSTRUCTION TIRES

EXCAVATOR

MAIN FEATURES

Special rubber compound that provides greater performance to the tire.

Tire designed for heavy duty, used by excavator and boom lift.

Tire design provides excellent traction , self-cleaning and good performance on the road.



APPLICATION:

TIRE SIZE	TRA CODE	PLY RATING	TYPE	RIM SIZE WIDTH	OVERALL DIAMETER		SECTION WIDTH		ROLLING CIRCUM ± 2.5%		TREAD DEPTH		MAX LOAD CAPACITY					
					(mm.)	(inch.)	(mm.)	(inch.)	(mm.)	(inch.)	(mm.)	(32nds)	LOAD		INFLATION PRESSURE		SPEED	
				(mm.)	(mm.)	(inch.)	(mm.)	(inch.)	(mm.)	(inch.)	(mm.)	(32nds)	(kg.)	(lbs)	(psi)	(Kpa)	(km/h)	(mph)
10.00-20	-	16	TT	7.50	1.075	42.3	277	10.9	3.175	125.0	24	30	3.000	6.600	109	750	50	30
10.00-20	-	18	TT	7.50	1.075	42.3	277	10.9	3.175	125.0	24	30	3.250	7.150	115	790	50	30