



GRIPMASTER

BIAS AGRICULTURAL TIRES


G-AGRI 170WD (FLOTATION)

MAIN FEATURES

Design suitable for off-road application in all weather conditions.

Designed to provide excellent traction for the driving wheels and are suitable for both agricultural implements, industrial and construction applications.

Tire has better load distribution and less soil compaction using proper calibration.



APPLICATION:

TIRE SIZE	TRA CODE	PLY RATING	TYPE	RIM SIZE WIDTH		OVERALL DIAMETER		SECTION WIDTH		ROLLING CIRCUM ± 2.5%		TREAD DEPTH		MAX LOAD CAPACITY					
				(pol.)	(mm.)	(inch.)	(mm.)	(inch.)	(mm.)	(inch.)	(mm.)	(32nds)	LOAD	INFLATION PRESSURE		SPEED			
					(mm.)	(inch.)	(mm.)	(inch.)	(mm.)	(inch.)	(mm.)	(32nds)	(kg.)	(lbs)	(psi)	(Kpa)	(km/h)	(mph)	
400/60-15.5	-	14	TL	13.00	875	34.4	400	15.7	2.565	101.0	20	25	2.731	6.020	52	358	40	25	
400/60-15.5	-	18	TL	13.00	875	34.4	400	15.7	2.565	101.0	20	25	3.256	7.170	65	448	40	25	
385/65-22.5	-	14	TL	11.75	1.070	42.1	385	15.2	3.226	127.0	22	28	2.120	4.675	45	310	50	30	
385/65-22.5	-	16	TL	11.75	1.070	42.1	385	15.2	3.226	127.0	22	28	2.240	4.940	51	351	50	30	
400/60-22.5	-	14	TL	11.75	1.070	42.1	400	15.7	3.226	127.0	22	28	2.120	4.675	45	310	50	30	
400/60-22.5	-	16	TL	11.75	1.070	42.1	400	15.7	3.226	127.0	22	28	2.240	4.940	51	351	50	30	
400/60-22.5	-	18	TL	11.75	1.070	42.1	400	15.7	3.226	127.0	22	28	2.504	5.520	55	379	50	30	
500/60-22.5	-	16	TL	16.00	1.170	46.1	500	19.7	3.480	137.0	38	48	3.156	6.950	41	282	50	30	
550/60-22.5	-	16	TL	16.00	1.240	48.8	550	21.7	3.738	147.2	38	48	3.356	7.930	45	310	50	30	