



**GRIPMASTER**

## BIAS AGRICULTURAL TIRES

### G-AGRI 610WD

#### MAIN FEATURES

Tire for agricultural tractors, specifically for regular traction wheels.

Tire has long and robust blocks with wide and deep grooves that provide greater traction power with resistance against skidding. In addition, it distributes the stresses evenly, generating greater resistance against damage.

Reinforced special compound that provides greater performance to the tire.



#### APPLICATION:

TIRE SIZE	TRA CODE	PLY RATING	TYPE	RIM SIZE WIDTH		OVERALL DIAMETER		SECTION WIDTH		ROLLING CIRCUM ± 2.5%		TREAD DEPTH		LOAD		INFLATION PRESSURE		SPEED	
				(pol.)	(mm.)	(inch.)	(mm.)	(inch.)	(mm.)	(inch.)	(mm.)	(32nds)	(kg.)	(lbs)	(psi)	(Kpa)	(km/h)	(mph)	
6-12	R-1	4	TT	4.00	585	23.0	153	6.0	1.735	68.3	16	20.2	315	695	34	235	30	20	
6-12	R-1	6	TT	4.00	585	23.0	153	6.0	1.735	68.3	16	20.2	345	760	36	250	30	20	
8.0/75-15	R-1	6	TT	6.5	708	27.9	199	7.8	2.093	82.4	20	25.2	1.100	2.425	49	337	40	25	
7.5L-15	R-1	6	TT	6	795	31.3	210	8.3	2.286	90.0	20	25.2	780	1.719	51	351	40	25	
6.5/80-15	R-1	6	TT	5	663	26.1	163	6.4	1.976	77.8	15	18.9	900	1.984	52	358	40	25	
5.00-15	R-1	6	TT	4	657	25.9	145	5.7	1.956	77.0	15	18.9	387	853	51	351	30	20	
8-16 (8.00-16)	R-1	8	TT	7	813	32.0	203	8.0	2.362	93.0	17	21.4	1.300	2.866	27	186	40	25	
7-16 (7.00-16)	R-1	6	TT	5.5	740	29.1	183	7.2	2.205	86.8	17	21.4	950	2.094	36	248	40	25	
5.00-16	R-1	6	TT	4	710	28.0	150	5.9	2.083	82.0	16	20.2	400	881	54	372	40	25	
4.50-16	R-1	6	TT	3	655	25.8	122	4.8	1.952	76.9	9	11.3	365	804	47	324	40	25	
4.00-16	R-1	6	TT	3	640	25.2	115	4.5	1.932	76.1	9	11.3	290	639	44	303	40	25	
4.50-19	R-1	4	TT	3	736	29.0	122	4.8	2.146	84.5	15	18.9	450	992	62	427	40	25	
8.00-20	R-1	6	TT	7.00	965	38	229	9	2.845	112	26	32.8	870	1.918	30	206	30	20	
11.2-20	R-1	8	TT	10.00	998	39.3	284	11.2	2.997	118	32	40.3	1.090	2.403	36	248	30	20	
5.00-21	R-1	6	TT	4	823	32.4	140	5.5	2.310	90.9	10	12.6	435	959	38	262	40	25	
4.00-21	R-1	6	TT	3	762	30.0	115	4.5	2.247	88.5	6	7.6	180	396	25	172	40	25	
9.5-24	R-1	8	TT	7.00	1.050	41.3	241	9.5	3.099	122	26	32.8	1.120	2.469	41	282	30	20	
12.4-24	R-1	6	TT	11.00	1.170	46.1	315	12.4	3.404	134	29	36.5	1.300	2.870	29	200	30	20	
12.4-24	R-1	8	TT	11.00	1.170	46.1	315	12.4	3.404	134	29	36.5	1.450	3.196	33	227	30	20	
12.4-24	R-1	12	TT	11.00	1.170	46.1	315	12.4	3.404	134	29	36.5	1.800	3.968	51	351	30	20	
13.6-24	R-1	8	TT	12.0	1.210	47.6	345	13.5	3.556	140.0	29	36	1.500	3.300	28	193	30	20	
13.6-24	R-1	12	TT	12.00	1.210	47.6	345	13.5	3.556	140.0	29	36	1.850	4.080	52	360	30	20	
14.9-24	R-1	8	TT	13.00	1.265	49.8	378	14.9	3.708	146	32	40.3	1.800	3.968	26	179	30	20	
14.9-24	R-1	12	TT	13.00	1.265	49.8	378	14.9	3.708	146	32	40.3	2.250	4.960	52	358	30	20	
13.6-26	R-1	8	TT	12.00	1.260	49.6	345	13.6	3.708	146	30	37.8	1.650	3.637	26	179	30	20	
14.9-26	R-1	8	TT	13.00	1.315	51.8	378	14.9	3.861	152	30	37.8	1.850	4.078	26	179	30	20	
14.9-26	R-1	12	TT	13.00	1.315	51.8	378	14.9	3.861	152	30	37.8	2.300	5.070	52	358	30	20	
23.1-26	R-1	12	TL/TT	20.0	1.580	62.2	588	23.2	4.616	43.00	43	54	3.650	8.030	25	170	30	20	
23.1-26	R-1	16	TL/TT	20.0	1.580	62.2	588	23.2	4.616	43.00	43	54	4.375	9.625	33	230	30	20	
8.3-28	R-1	8	TT	7	1.095	43.1	211	8.3	3.251	128.0	27	34.0	1.000	2.204	34	234	40	25	
12.4-28	R-1	8	TT	11.00	1.265	49.8	378	14.9	3.708	146	32	40.3	1.550	3.420	33	230	30	20	
12.4-28	R-1	10	TT	11.00	1.265	49.8	378	14.9	3.708	146	32	40.3	1.650	3.640	35	240	30	20	
14.9-28	R-1	8	TT	13.00	1.365	53.7	378	14.9	4.013	158	33	41.6	1.900	4.188	26	179	30	20	
14.9-28	R-1	12	TT	13.00	1.365	53.7	378	14.9	4.013	158	33	41.6	2.300	5.070	37	255	30	20	
16.9-28	R-1	8	TT	15.00	1.435	56.5	429	16.9	4.216	166	35	44.1	2.180	4.806	26	179	30	20	
16.9-28	R-1	12	TT	15.00	1.435	56.5	429	16.9	4.216	166	35	44.1	2.725	6.007	34	234	30	20	
7.2-30	R-1	8	TT	6	1.095	43.1	183	7.2	3.225	127.0	27	34.0	800	1.763	39	268	40	25	

## BIAS AGRICULTURAL TIRES

### G-AGRI 610WD

#### MAIN FEATURES

Tire for agricultural tractors, specifically for regular traction wheels.

Tire has long and robust blocks with wide and deep grooves that provide greater traction power with resistance against skidding. In addition, it distributes the stresses evenly, generating greater resistance against damage.

Reinforced special compound that provides greater performance to the tire.



#### APPLICATION:

TIRE SIZE	TRA CODE	PLY RATING	TYPE	RIM SIZE WIDTH	OVERALL DIAMETER		SECTION WIDTH		ROLLING CIRCUM ± 2.5%		TREAD DEPTH		MAX LOAD CAPACITY					
													LOAD		INFLATION PRESSURE		SPEED	
													(kg.)	(lbs)	(psi)	(Kpa)	(km/h)	(mph)
4.00-30	R-1	4	TT	3	995	39.2	116	4.6	2.938	115.7	12	15.1	350	771	18	124	40	25
18.4-30	R-1	8	TT	16.00	1.560	61.4	467	18.4	4.547	179	38	47.9	2.436	5.370	20	137	30	20
18.4-30	R-1	10	TT	16.00	1.560	61.4	467	18.4	4.547	179	38	47.9	2.650	5.842	23	158	30	20
18.4-30	R-1	12	TT	16.00	1.560	61.4	467	18.4	4.547	179	38	47.9	3.257	7.180	33	227	30	20
18.4-30	R-1	14	TT	16.00	1.560	61.4	467	18.4	4.547	179	38	47.9	3.450	7.605	39	268	30	20
8.3-32	R-1	8	TT	7	1.193	47.0	211	8.3	3.581	141.0	30	37.8	1.090	2.403	45	310	40	25
9.5-32	R-1	8	TT	8	1.255	49.4	241	9.5	3.683	145.0	30	37.8	1.060	2.336	50	344	40	25
12.4-32	R-1	8	TT	11.00	1.359	53.5	325	12.8	3.988	157	34	42.8	1.655	3.648	33	227	30	20
18.4-34	R-1	8	TT	16.00	1.660	65.4	467	18.4	4.851	191	38	47.9	2.650	5.842	20	137	30	20
18.4-34	R-1	12	TT	16.00	1.660	65.4	467	18.4	4.851	191	38	47.9	3.430	7.561	33	227	30	20
18.4-34	R-1	14	TT	16.00	1.660	65.4	467	18.4	4.851	191	38	47.9	3.750	8.267	38	262	30	20
20.8-34	R-1	14	TT	18.00	1.760	69.3	528	20.8	5.156	203	38	47.9	3.200	7.054	20	137	30	20
20.8-34	R-1	18	TT	18.00	1.760	69.3	528	20.8	5.156	203	38	47.9	3.650	8.046	26	179	30	20
9.5-36	R-1	8	TT	8	1.359	53.5	241	9.5	4.000	157.5	31	39.1	1.500	3.306	51	351	40	25
8.3-36	R-1	8	TT	7	1.293	50.9	211	8.3	3.810	150.0	28	35.3	1.150	2.535	45	310	40	25
7.2-36	R-1	8	TT	6	1.255	49.4	183	7.2	3.810	150.0	30	37.8	1.005	2.215	53	365	40	25
5.00-36	R-1	4	TT	3	1.175	46.3	145	5.7	3.456	136.1	12	15.1	380	837	32	220	40	25
4.50-36	R-1	4	TT	3	1.150	45.3	135	5.3	3.402	133.9	12	15.1	390	859	32	220	40	25
4.00-36	R-1	4	TT	3	1.140	44.9	120	4.7	3.364	132.4	12	15.1	330	727	32	220	40	25
12.4-36	R-1	8	TT	11	1.465	57.7	315	12.4	4.318	170.0	28	35.3	1.750	3.858	33	227	40	25
9.5-38	R-1	8	TT	8	1.405	55.3	241	9.5	4.147	163.3	31	39.1	1.800	3.968	43	296	40	25
8.3-38	R-1	8	TT	7	1.350	53.1	211	8.3	3.986	156.9	31	39.1	1.250	2.755	50	344	40	25
12.4-38	R-1	8	TT	11	1.511	59.5	315	12.4	4.496	177	32	40.3	1.750	3.858	38	262	40	25
14.9-38	R-1	12	TL	14.00	1.685	66.3	378	14.9	4.597	181	40	50.4	2.575	5.676	43	296	30	20
18.4-38	R-1	8	TT	16.00	1.770	69.7	467	18.4	5.156	203	38	47.9	2.725	6.010	20	140	30	20
18.4-38	R-1	10	TT	16.00	1.770	69.7	467	18.4	5.156	203	38	47.9	2.840	6.260	25	170	30	20
18.4-38	R-1	14	TT	16.00	1.770	69.7	467	18.4	5.156	203	38	47.9	3.650	8.045	33	230	30	20
20.8-38	R-1	8	TT	18.00	1.834	72.2	531	20.9	5.385	212	40	50.4	3.150	6.944	19	131	30	20
20.8-38	R-1	12	TT	18.00	1.834	72.2	531	20.9	5.385	212	40	50.4	4.000	8.818	29	199	30	20
20.8-38	R-1	14	TT	18.00	1.840	72.4	528	20.8	5.385	212	40	50.4	4.500	9.920	36	248	30	20