



**GRIPMASTER**

## BIAS AGRICULTURAL TIRES

### G-AGRI 710WD

#### MAIN FEATURES

Tire multi-spoke for application on tractor and implement free axles.

Tire has deep and symmetrical grooves with wide shoulders that provide self-cleaning and greater stability.

Flat tread ensures better load distribution and less soil compaction, ensuring better harvesting and planting.



TIRE SIZE	TRA CODE	PLY RATING	TYPE	RIM SIZE WIDTH	OVERALL DIAMETER		SECTION WIDTH		ROLLING CIRCUM ± 2.5%		TREAD DEPTH		MAX LOAD CAPACITY					
					(pol.)	(mm.)	(inch.)	(mm.)	(inch.)	(mm.)	(inch.)	(mm.)	(32nds)	LOAD	INFLATION PRESSURE		SPEED	
													(kg.)	(lbs)	(psi)	(Kpa)	(km/h)	(mph)
9.5L-14	I-1	8	TL	7.00	735	28.9	240	9.4	2.159	85.0	6	7	1.090	2.398	43	296	65	40
11L-14	I-1	8	TL	8.00	746	29.4	274	10.8	2.209	87.0	7	7	1.125	2.475	36	248	65	40
5.90-15	I-1	4	TL	4.50	657	25.9	152	6.0	1.955	77.0	5	6	522	1.150	36	248	65	40
6.70-15	I-1	6	TL	4.50	703	27.7	167	6.6	2.082	82.0	5	6	730	1.606	43	296	65	40
7.60-15	I-1	6	TL	5.50	718	28.3	190	7.5	2.184	86.0	5	6	800	1.760	41	283	65	40
9.5L-15	I-1	8	TL	7.00	765	30.1	241	9.5	2.235	88.0	6	8	1.090	2.398	43	296	65	40
9.5L-15	I-1	12	TL	7.00	765	30.1	241	9.5	2.235	88.0	6	8	1.250	2.750	46	317	65	40
11L-15	I-1	8	TL	8.00	790	31.1	270	10.6	2.261	89.0	8	10	1.150	2.530	36	248	65	40
11L-15	I-1	12	TL	8.00	790	31.1	270	10.6	2.261	89.0	8	10	1.450	3.190	51	352	65	40
12.5L-15	I-1	8	TL	10.00	818	32.2	310	12.2	2.413	95.0	9	11	1.360	2.992	36	248	65	40
12.5L-15	I-1	12	TL	10.00	818	32.2	310	12.2	2.413	95.0	9	11	1.750	3.850	52	359	65	40
12.5L-15	I-1	16	TL	10.00	818	32.2	310	12.2	2.413	95.0	9	11	2.023	4.450	65	448	65	40
31x13.50-15	I-1	8	TL	10.00	779	30.7	347	13.7	2.134	84.0	9	11	1.181	2.600	45	310	65	40
31x13.50-15	I-1	12	TL	10.00	779	30.7	347	13.7	2.134	84.0	9	11	1.600	3.520	75	517	65	40
6.00-16	I-1	8	TL	4.50	720	28.3	165	6.5	2.134	84.0	7	9	690	1.518	43	296	65	40
6.50-16	I-1	8	TL	4.50	750	29.5	175	6.9	2.134	84.0	7	9	710	1.560	40	275	65	40
6.50-16	I-1	10	TL	4.50	750	29.5	175	6.9	2.134	84.0	7	9	800	1.760	43	295	65	40
7.50-16	I-1	10	TL	5.50	785	30.9	205	8.1	2.311	91.0	7	9	1.120	2.450	52	360	65	40
9.00-16	I-1	8	TL	6.50	845	33.3	234	9.2	2.490	98.0	9	11	1.360	3.000	50	345	65	40
9.00-16	I-1	10	TL	6.50	845	33.3	234	9.2	2.490	98.0	9	11	1.500	3.310	52	360	65	40
12.5L-16	I-1	8	TL	10.00	845	33.2	310	12.2	2.464	97.0	8	10	1.470	3.240	36	248	65	40
12.5L-16	I-1	12	TL	10.00	845	33.2	310	12.2	2.464	97.0	8	10	1.800	3.960	52	359	65	40
14L-16.1	I-1	8	TL	11.00	927	36.5	355	14.0	2.565	101.0	9	11	1.800	3.960	33	228	65	40
14L-16.1	I-1	12	TL	11.00	927	36.5	355	14.0	2.565	101.0	9	11	2.120	4.664	44	303	65	40
16.5L-16.1	I-1	10	TL	14.00	1.023	40.3	434	17.1	2.794	110.0	12	15	2.360	5.192	36	248	50	30
16.5L-16.1	I-1	14	TL	14.00	1.023	40.3	434	17.1	2.794	110.0	12	15	2.820	6.210	61	421	50	30
19.5L-16.1	I-1	12	TL	16.00	1.023	40.3	490	19.3	2.921	115.0	12	15	2.725	5.995	31	214	50	30
21.5L-16.1	I-1	10	TL	18.00	1.102	43.4	533	21.0	3.048	120.0	12	15	3.000	6.600	27	186	50	30
21.5L-16.1	I-1	14	TL	18.00	1.102	43.4	533	21.0	3.048	120.0	12	15	3.550	7.810	36	248	50	30