



GRIPMASTER

BIAS CONSTRUCTION TIRES

G-EARTH 640WD

MAIN FEATURES

Tires for agricultural and industrial tractors specially for traction and rear wheel for backhoe.

Design that provides extra traction with a carcass shape that, in addition to providing comfort in handling, offers greater resistance and resistance to damage.

Special and reinforced rubber compound that provides greater performance to the tyre.



APPLICATION:



TIRE SIZE	TRA CODE	PLY RATING	TYPE	RIM SIZE WIDTH	OVERALL DIAMETER				ROLLING CIRCUM ± 2.5%		TREAD DEPTH		MAX LOAD CAPACITY					
					(mm.)	(inch.)	(mm.)	(inch.)	(mm.)	(inch.)	(mm.)	(32nds)	LOAD		INFLATION PRESSURE		SPEED	
				(pol.)	(mm.)	(inch.)	(mm.)	(inch.)	(mm.)	(inch.)	(mm.)	(32nds)	(kg.)	(lbs)	(psi)	(Kpa)	(km/h)	(mph)
10.5-18	R-4	12	TL	9.00	904	35.6	269	10.6	2.692	106	21	26	2.200	4.850	62	427	40	25
18-19.5	R-4	16	TL	14.00	1.105	43.5	460	18.1	3.277	129	25	31	4.500	9.900	85	586	40	25
18-19.5	R-4	18	TL	14.00	1.105	43.5	460	18.1	3.277	129	25	31	5.150	11.330	102	703	40	25
10.5-20	R-4	10	TL	9.00	955	37.6	269	10.6	2.870	113	21	26	1.800	3.960	54	372	40	25
12.5-20	R-4	10	TL	11.00	1.039	40.9	325	12.8	3.099	122	21	26	1.850	4.070	43	296	40	25
12.5-20	R-4	12	TL	11.00	1.039	40.9	325	12.8	3.099	122	21	26	2.000	4.400	51	352	40	25
12.5-20	R-4	16	TL	11.00	1.039	40.9	325	12.8	3.099	122	21	26	2.300	5.071	68	469	40	25
12.5-20	R-4	18	TL	11.00	1.039	40.9	325	12.8	3.099	122	21	26	2.725	6.010	55	380	40	25
14.5-20	R-4	12	TL	11.00	1.115	43.9	361	14.2	3.302	130	25	31	2.230	4.916	45	310	40	25
14.5-20	R-4	14	TL	11.00	1.115	43.9	361	14.2	3.302	130	25	31	2.430	5.346	51	352	40	25
14.5-20	R-4	18	TL	11.00	1.115	43.9	361	14.2	3.302	130	25	31	2.725	5.995	63	434	40	25