

BIAS CONSTRUCTION TIRES

G-EARTH 641WD

MAIN FEATURES

Tires for agricultural and industrial tractors specially for traction and rear wheel for backhoe.

Design that provides extra traction with a carcass shape that, in addition to providing comfort in handling, offers greater resistance and resistance to damage.

Special and reinforced rubber compound that provides greater performance to the tyre.



TIRE SIZE	TRA CODE	PLY RATING	TYPE	RIM SIZE WIDTH	OVERALL DIAMETER		SECTION WIDTH		ROLLING CIRCUM ± 2.5%		TREAD DEPTH		MAX LOAD CAPACITY					
					(mm.)	(inch.)	(mm.)	(inch.)	(mm.)	(inch.)	(mm.)	(32nds)	LOAD		INFLATION PRESSURE		SPEED	
													(kg.)	(lbs)	(psi)	(Kpa)	(km/h)	(mph)
18.4-24	R-4	12	TL	16.00	1.375	54.1	472	18.6	4.039	159.0	28	35	3.875	8.525	35	241	40	25
16.9-24	R-4	12	TL	15.00	1.308	51.5	440	17.3	3.861	152.0	28	35	3.250	7.150	38	262	40	25
19.5L-24	R-4	12	TL	17.00	1.321	52.1	495	19.5	3.835	151.0	28	35	3.450	7.590	33	228	40	25
19.5L-24	R-4	16	TL	17.00	1.325	51.9	495	19.5	3.835	151.0	28	35	4.135	9.097	44	303	40	25
21L-24	R-4	12	TL	18.00	1.377	54.2	533	24.0	3.988	157.0	29	36	3.875	8.525	31	214	40	25
21L-24	R-4	16	TL	18.00	1.377	54.2	533	24.0	3.988	157.0	29	36	4.500	9.920	38	262	40	25
18.4-26	R-4	12	TL	16.00	1.425	56.1	475	18.7	4.191	165.0	28	38	4.000	8.800	36	248	40	25
18.4-26	R-4	16	TL	16.00	1.425	56.1	475	18.7	4.191	165.0	28	38	4.375	9.625	41	283	40	25
16.9-28	R-4	12	TL	15.00	1.410	55.5	440	17.3	4.140	163.0	30	38	3.550	7.810	38	262	40	25