



GRIPMASTER

BIAS INDUSTRIAL TIRES

G-IND 230

MAIN FEATURES

Development for intermediate operations.

Tread allows for better traction and performance.

Double bead to prevent air leakage at the wheel, allowing the tires to stay calibrated for much longer.

Suitable for indoor and outdoor, clean and level floors.



APPLICATION:

TIRE SIZE	PLY RATING	TYPE	RIM SIZE WIDTH	OVERALL DIAMETER		SECTION WIDTH		TREAD DEPTH		MAX LOAD CAPACITY																INFLATED PRESSURE	
										Counterbalanced Lift Trucks								Other Industrial Vehicles									
										25 km/h				35 km/h				10 km/h		25 km/h		40 km/h		50 km/h			
										DRIVE		STEER		DRIVE		STEER		(kg.)	(lbs.)	(kg.)	(lbs.)	(kg.)	(lbs.)	(kg.)	(lbs.)		
(pol.)	(mm.)	(inch.)	(mm.)	(inch.)	(mm.)	(inch.)	(mm.)	(32nds)	(kg.)	(lbs.)	(kg.)	(lbs.)	(kg.)	(lbs.)	(kg.)	(lbs.)	(kg.)	(lbs.)	(kg.)	(lbs.)	(psi.)	(Kpa)					
4.00-8	8	TT	3.00D	414	16.3	112	4.4	7	9	870	1.920	670	1.475	840	1.850	620	1.365	870	1.920	670	1.475	595	1.310	565	1.250	131	900
4.00-8	10	TT	3.00D	414	16.3	112	4.4	7	9	950	2.095	730	1.610	915	2.020	675	1.490	950	2.095	730	1.610	650	1.435	615	1.360	145	1.000
5.00-8	8	TT	3.50D-8	467	18.4	132	5.2	10	13	1.235	2.720	950	2.095	1.190	2.625	880	1.940	1.235	2.720	950	2.095	845	1.865	800	1.765	120	825
5.00-8	10	TT	3.50D-8	467	18.4	132	5.2	10	13	1.415	3.120	1.090	2.400	1.365	3.010	1.010	2.230	1.415	3.120	1.090	2.400	970	2.140	915	2.020	145	1.000
6.00-9	10	TT	4.00E	540	21.3	160	6.3	11	14	1.715	3.780	1.320	2.910	1.650	3.640	1.220	2.690	1.715	3.780	1.320	2.910	1.175	2.590	1.110	2.450	123	850
6.00-9	12	TT	4.00E	540	21.3	160	6.3	11	14	1.885	4.155	1.450	3.200	1.815	4.000	1.345	2.965	1.885	4.155	1.450	3.200	1.290	2.845	1.220	2.690	145	1.000
6.50-10	10	TT	5.00F	588	23.1	177	7.0	11	14	1.950	4.300	1.500	3.310	1.875	4.135	1.390	3.065	1.950	4.300	1.500	3.310	1.335	2.940	1.260	2.780	112	775
6.50-10	12	TT	5.00F	588	23.1	177	7.0	11	14	2.145	4.730	1.650	3.640	2.065	4.555	1.525	3.360	2.145	4.730	1.650	3.640	1.470	3.240	1.390	3.065	131	900
7.00-12	12	TT	5.00S-12	672	26.5	192	7.6	12	15	2.680	5.910	2.060	4.540	2.575	5.680	1.905	4.200	2.680	5.910	2.060	4.540	1.835	4.045	1.730	3.815	123	850
7.00-12	14	TT	5.00S-12	672	26.5	192	7.6	12	15	2.755	6.075	2.120	4.675	2.650	5.845	1.960	4.320	2.755	6.075	2.120	4.675	1.885	4.155	1.780	3.925	131	900
7.00-15	12	TT	5.5-15	746	29.4	197	7.8	14	18	3.070	6.770	2.360	5.200	2.950	6.500	2.185	4.815	3.070	6.770	2.360	5.200	2.100	4.630	1.985	4.380	120	825
7.00-15	14	TT	5.5-15	746	29.4	197	7.8	14	18	3.350	7.385	2.575	5.680	3.220	7.100	2.385	5.260	3.350	7.385	2.575	5.675	2.290	5.050	2.165	4.775	131	900
7.50-10	12	TT	5.50F	645	25.4	207	8.1	15	19	2.340	5.160	1.800	3.970	2.250	4.960	1.665	3.670	2.340	5.160	1.800	3.970	1.600	3.530	1.510	3.330	94	650
7.50-15	14	TT	6.0-15	772	30.4	212	8.3	15.5	20	3.640	8.025	2.800	6.175	3.500	7.715	2.590	5.710	3.640	8.025	2.800	6.175	2.490	5.490	2.350	5.180	134	925
8.25-15	12	TT	6.5	836	32.9	234	9.2	18	23	3.900	8.600	3.000	6.615	3.750	8.265	2.775	6.120	3.900	8.600	3.000	6.615	2.670	5.880	2.520	5.560	102	700
8.25-15	14	TT	6.5	836	32.9	234	9.2	18	23	4.225	9.315	3.250	7.165	4.065	8.960	3.005	6.625	4.225	9.315	3.250	7.165	2.895	6.380	2.730	6.020	116	800
8.25-15	18	TT	6.5	836	32.9	234	9.2	18	23	4.745	10.460	3.650	8.050	4.565	10.065	3.375	7.440	4.745	10.460	3.650	8.050	3.250	7.165	3.065	6.760	145	1.000
18x7-8	14	TT	4.33R-8	462	18.2	173	6.8	12	15	1.885	4.150	1.450	3.200	1.815	4.000	1.340	2.955	1.885	4.160	1.450	3.200	1.290	2.845	1.215	2.680	131	900
18x7-8	16	TT	4.33R-8	462	18.2	173	6.8	12	15	2.145	4.730	1.650	3.640	2.065	4.555	1.525	3.360	2.145	4.730	1.650	3.640	1.470	3.240	1.385	3.055	145	1.000
21x8-9	14	TT	6.00E-09	535	21.1	200	7.9	13	16	2.535	5.590	1.950	4.300	2.440	5.380	1.805	3.980	2.535	5.590	1.950	4.300	1.735	3.825	1.640	3.620	131	900
21x8-9	16	TT	6.00E-09	535	21.1	200	7.9	13	16	2.755	6.075	2.120	4.675	2.650	5.840	1.960	4.320	2.755	6.075	2.120	4.675	1.885	4.150	1.780	3.925	145	1.000
23x9-10	16	TT	6.50F	595	23.4	225	8.9	13.5	17	2.990	6.590	2.300	5.070	2.875	6.340	2.130	4.700	2.990	6.590	2.300	5.070	2.045	4.510	1.935	4.270	116	800
23x9-10	18	TT	6.50F	595	23.4	225	8.9	13.5	17	3.160	6.965	2.430	5.360	3.040	6.700	2.250	4.960	3.160	6.965	2.430	5.360	2.165	4.775	2.040	4.500	131	900
27x10-12	14	TT	8.00G-12	690	27.2	255	10.0	15	19	3.545	7.815	2.725	6.010	3.405	7.510	2.520	5.560	3.545	7.815	2.725	6.010	2.425	5.350	2.290	5.050	102	700
28x9-15	12	TT	7.0	707	27.8	216	8.5	18.5	23	3.445	7.595	2.650	5.845	3.315	7.310	2.450	5.400	3.445	7.595	2.650	5.845	2.360	5.200	2.225	4.900	120	825
28x9-15	14	TT	7.0	707	27.8	216	8.5	18.5	23	3.900	8.600	3.000	6.615	3.750	8.265	2.775	6.120	3.900	8.600	3.000	6.615	2.670	5.890	2.520	5.560	145	1.000
250-15	16	TT	7.5	735	28.9	250	9.8	19	24	4.355	9.600	3.350	7.385	4.190	9.240	3.100	6.835	4.355	9.600	3.350	7.385	2.980	6.570	2.815	6.210	120	825
250-15	18	TT	7.5	735	28.9	250	9.8	19	24	4.745	10.460	3.650	8.050	4.565	10.065	3.375	7.440	4.745	10.460	3.650	8.050	3.250	7.165	3.065	6.760	138	950
300-15	20	TT	8.0	840	33.1	300	11.8	22	28	6.500	14.330	5.000	11.020	6.250	13.780	4.625	10.200	6.500	14.330	5.000	11.020	4.450	9.810	4.200	9.260	131	900