

RADIAL INDUSTRIAL TIRES

G-PREMIUM

MAIN FEATURES

Developed for heavy operations on forklifts and other industrial vehicle.

High quality compound and exclusive design that offers excellent adhesion.

Extra width and depth provides excellent traction, durability and puncture resistance.





TIRE SIZE	PLY RATING	TYPE	RIM SIZE WIDHT	OVERALL DIAMETER		SECTION WIDHT		TREAD DEPTH		MAX LOAD CAPACITY		INFLATION PRESSURE		SPEED	
			(pol.)	(mm.)	(inch.)	(mm.)	(inch.)	(mm.)	(32nds.)	(kg.)	(lbs.)	(psi.)	(Kpa)	(km/h)	(mph)
5.00R8	**	TL	3.50	460	18.1	135	5.3	23	29	1.090	2.400	145	1.000	25	15
6.00R9	**	TL	4.00	525	20.7	160	6.3	24	30	1.450	3.200	145	1.000	25	15
6.50R10	**	TL	5.00	585	23,0	182	7.2	27	34	1.800	3.970	145	1.000	25	15
7.00R12	**	TL	5.00	670	26.4	195	7.7	28	35	2.240	4.940	145	1.000	25	15
7.50R15	**	TL	5.50	770	30.3	210	8.3	28	35	3.000	6.610	145	1.000	25	15
8.25R15	**	TL	6.50	835	32.9	240	9.4	33	42	3.650	8.050	145	1.000	25	15
28X9R15	**	TT	7.00	719	28.3	233	9.2	25	31	3.250	7.165	145	1.000	25	15