

BIAS AGRICULTURAL TIRES

G-PRO AGRI 610GD

MAIN FEATURES

Tire selected for applications in tractors, harvesters and implements.

Tread designed to provide excellent traction and self-cleaning.



APPLICATION:



TIRE SIZE	TRA CODE	PLY RATING	TYPE	RIM SIZE WIDTH	OVERALL DIAMETER		SECTION WIDTH		TREAD DEPTH		MAX LOAD CAPACITY					
											LOAD		INFLATION PRESSURE		SPEED	
											(kg.)	(lbs)	(psi)	(Kpa)	(km/h)	(mph)
6.00-16	R-1	6	TT	4.50	745	29.3	165	6.4	26	32.7	495	1.090	36	248	30	20
6.00-16	R-1	8	TT	4.50	745	29.3	165	6.4	26	32.7	550	1.210	52	358	30	20
6.50-16	R-1	6	TT	5.00	765	30.1	180	7	26	32.7	565	1.240	36	248	30	20
7.50-16	R-1	6	TT	5.50	810	31.8	205	8	26	32.7	650	1.430	30	206	30	20
7.50-16	R-1	8	TT	5.50	810	31.8	205	8	26	32.7	750	1.650	42	289	30	20
9.5-20	R-1	8	TT	8.00	950	37.4	240	9.4	30	37.8	955	2.100	41	280	30	20
8.3-24	R-1	6	TT	7.00	995	39.2	210	8.3	28	35.3	810	1.780	35	240	30	20
9.5-24	R-1	6	TT	8.00	1.050	41.3	240	9.4	30	37.8	940 / 850	2.070 / 1.870	30 / 30	210 / 210	30 / 40	20 / 25
11.2-24	R-1	6	TT	10.00	1.105	43.5	285	11.2	35.5	39.1	1.045 / 950	2.300 / 2.090	26 / 26	180 / 180	30 / 40	20 / 25
11.2-24	R-1	8	TT	10.00	1.105	43.5	285	11.2	35.5	39.1	1.225	2.700	35	240	30	20
11.2-24	R-1	10	TT	10.00	1.105	43.5	285	11.2	35.5	39.1	1.380	3.040	43	300	30	20
12.4-24	R-1	8	TL	11.00	1.160	45.7	315	12.4	30	37.8	1.415 / 1.285	3.120 / 2.830	33 / 32	230 / 220	30 / 40	20 / 25
14.9-24	R-1	8	TT	13.00	1.265	49.8	380	15.0	35	44.1	1.760 / 1.600	3.880 / 3.520	26 / 26	180 / 180	30 / 40	20 / 25
23.1-26	R-1	18	TL	20.00	1.605	63.2	590	23.2	42.6	53.7	4.125	9.094	36	248	40	25
11.2-28	R-1	8	TT	10.00	1.205	47.4	285	11.2	31	39.1	1.305	2.877	35	241	30	20
12.4-28	R-1	8	TT	11.00	1.260	49.6	315	12.4	33	41.6	1.415 / 1.285	3.120 / 2.830	33 / 32	230 / 220	30	20
13.6-28	R-1	10	TT	12.00	1.310	51.6	345	13.6	34	42.8	1.910 / 1.700	4.210 / 3.740	36 / 36	250 / 250	30 / 40	20 / 25
14.9-28	R-1	8	TT	13.00	1.365	53.7	380	15.0	35	44.1	1.880 / 1.700	4.145 / 3.740	26 / 26	180 / 180	30 / 40	20 / 25
23.1-30	R-1	12	TT	20.00	1.705	67.1	587	23.1	37	46.6	3.850	8.490	25	170	30	20
24.5-32	R-1	16	TT	21.00	1.805	71.1	625	24.6	39	49.1	4.750	10.470	32	220	40	25
16.9-34	R-1	10	TT	15.00	1.585	62.4	430	16.9	35	44.1	2.605 / 2.360	5.740 / 5.200	29 / 28	200 / 190	30 / 40	20 / 25