

BIAS MINING TIRES

G-PRO MINE 250GD (L-5)

MAIN FEATURES

Reinforced shoulders and sidewall provide high performance in severe conditions.

Robust tire provides extreme stability and resistance to cuts and punctures, suitable for mining and ceramic operations.



TIRE SIZE	TRA CODE	PLY RATING	TYPE	RIM SIZE WIDTH			SECTION WIDTH		ROLLING CIRCUM ± 2.5%		TREAD DEPTH		MAX LOAD CAPACITY					
				(psi)	(mm)	(inch)	(mm)	(inch)	(mm)	(32nds)	LOAD		INFLATION PRESSURE		SPEED			
20.5-25	L-5	20	TL	17.00/2.00	1.548	60.9	520	20.5	4.536	179	80.0	100.8	9.500	20.900	65	450	10	5
23.5-25	L-5	20	TL	19.00/2.5	1.673	65.9	595	23.4	4.902	193	90.0	113.4	10.900	24.000	54	375	10	5
26.5-25	L-5	28	TL	22.00/3.0	1.798	70.8	675	26.6	5.268	207	100.0	126.0	15.500	34.200	69	475	10	5
29.5-25	L-5	28	TL	25.00/3.5	1.923	75.7	750	29.5	5.634	222	110.0	138.6	17.500	38.600	62	425	10	5
35/65-33	L-5	42	TL	28.00/3.5	2.077	81.8	889	35.0	6.086	240	82.0	103.3	25.000	55.100	83	575	10	5