



GRIPMASTER

SOLID INDUSTRIAL TIRES

GRIPMASTER HP

MAIN FEATURES

Unique design for reduced rolling resistance and vibrations.

Tread provides outstanding puncture resistance and long service life for up to 3 work shifts, up to 600 meter round trip distance and indoor and outdoor yards.

Produced with high-performance compounds, they increase the useful life of tires. Limited use speed at 25 km/h.



APPLICATION:



TIRE SIZE	RIM SIZE WIDTH	OVERALL DIAMETER		SECTION WIDTH		TREAD DEPTH		MAX LOAD CAPACITY								OTHER EQUIPMENTS	
								COUNTERBALANCED FORKLIFT									
								10 km/h				16 km/h					
								DRIVER		STEER		DRIVER		STEER			
(pol)	(mm)	(inch.)	(mm)	(inch.)	(mm)	(32nds.)	(kg)	(lbs.)	(kg)	(lbs.)	(kg)	(lbs.)	(kg)	(lbs.)	10 km/h		
6.00-9	4.00	545	21.5	160	6.3	24	30	1.975	4.350	1.520	3.350	1.805	3.980	1.390	3.070	1.520	3.350
6.50-10	5.00	597	23.5	178	7.0	28	35	2.715	5.990	2.090	4.610	2.485	5.480	1.910	4.210	2.095	4.620
7.00-12	5.00	683	26.9	192	7.6	29	37	3.105	6.845	2.390	5.270	2.835	6.250	2.180	4.810	2.390	5.270
28*9-15	7.00	706	27.8	225	8.9	35	44	4.060	8.950	3.125	6.890	3.710	8.180	2.855	6.300	3.125	6.890
8.25-15	6.50	847	33.3	236	9.3	38	48	5.085	11.210	3.910	8.620	4.640	10.230	3.570	7.870	3.910	8.620