



GRIPMASTER

SOLID INDUSTRIAL TIRES

IND CARGO PLUS

MAIN FEATURES

Industrial use tire with limited speeds of up to 15km/h and robust design offering great traction.

Provides stability, resistance to cuts and punctures and reduces maintenance time. Furthermore, they offer enormous carrying capacity.

Tire indicated for operations of up to 2 shifts, maximum cycles of 400 meters round trip, for internal and external yards with clean and level floors.



APPLICATION:

TIRE SIZE	RIM SIZE WIDTH	OVERALL DIAMETER		SECTION WIDTH				TREAD DEPTH								MAX LOAD CAPACITY						OTHER FORKLIFT							
																COUNTERBALANCED FORKLIFT													
																10 km/h				16 km/h				26 km/h				16 KM/H	
																DRIVER		STEER		DRIVER		STEER		DRIVER		STEER			
(pol)	(mm)	(inch.)	(mm)	(inch.)	(mm)	(32nds.)	(kg.)	(lbs.)	(kg.)	(lbs.)	(kg.)	(lbs.)	(kg.)	(lbs.)	(kg.)	(lbs.)	(kg.)	(lbs.)	(kg.)	(lbs.)									
2.50-15	7.50	693	27.3	228	9	43	54	5.315	11.720	4.090	9.020	4.855	10.700	3.735	8.230	4.510	9.940	3.470	7.650	3.875	8.540								
3.00-15	8.00	788	31	238	9.4	44	55	6.550	14.440	5.040	11.110	5.985	13.200	4.603	10.150	5.558	12.250	4.275	9.425	4.779	10.530								
7.50-15	5.50	752	29.6	189	7.4	40	50	3.690	8.135	2.950	6.500	3.425	7.550	2.570	5.670	3.190	7.030	2.395	5.280	2.450	5.400								



GRIPMASTER

SOLID INDUSTRIAL TIRES

IND CARGO PLUS

MAIN FEATURES

Industrial use tire with limited speeds of up to 15km/h and robust design offering great traction.

Provides stability, resistance to cuts and punctures and reduces maintenance time. Furthermore, they offer enormous carrying capacity.

Tire indicated for operations of up to 2 shifts, maximum cycles of 400 meters round trip, for internal and external yards with clean and level floors.



APPLICATION:

TIRE SIZE	RIM SIZE WIDHT	OVERALL DIAMETER		SECTION WIDHT		TREAD DEPHT		MAX LOAD CAPACITY												OTHER FORKLIFT	
								COUNTERBALANCED FORKLIFT												16 KM/H	
								10 km/h				16 km/h				26 km/h					
								DRIVER		STEER		DRIVER		STEER		DRIVER		STEER			
(pol)	(mm)	(inch.)	(mm)	(inch.)	(mm)	(32nds.)	(kg.)	(lbs.)	(kg.)	(lbs.)	(kg.)	(lbs.)	(kg.)	(lbs.)	(kg.)	(lbs.)	(kg.)	(lbs.)	(kg.)	(lbs.)	
5.00-8	3.00	455	17.9	125	4.9	35	44	1.190	2.620	920	2.030	1.090	2.400	835	1.840	1.005	2.215	775	1.710	910	2.000
18x7-8	4.33	440	17.3	155	6.1	35	44	2.350	5.180	1.880	4.140	2.265	5.000	1.700	3.750	2.110	4.650	1.585	3.500	1.620	3.570
6.00-9	4.00	515	20.3	143	5.6	39	49	1.876	4.130	1.444	3.180	1.715	3.780	1.321	2.910	1.591	3.500	1.226	2.700	1.368	3.020
6.50-10	5.00	566	22.3	153	6	45	57	2.580	5.690	1.985	430	2.360	5.200	1.815	4.000	2.195	4.840	1.685	3.715	1.885	4.150
7.00-12	5.00	643	25.3	176	6.9	42	53	2.950	6.500	2.270	5.000	2.693	5.930	2.071	4.565	2.503	5.520	1.924	4.240	2.271	5.000
8.25-15	6.50	810	31.9	204	8	47	59	4.830	10.650	3.715	8.190	4.408	9.720	3.392	7.480	4.095	9.030	3.149	6.940	3.520	7.760
28X9-15	7.00	691	27.2	208	8.2	38	48	3.857	8.500	2.969	6.540	3.525	7.770	2.712	5.980	3.273	7.220	2.518	5.550	2.813	6.200