



# GRIPMASTER

## SOLID MULTI-PURPOSE TIRES

### IND CARGO PREMIUM

MAIN FEATURES
Superelastic tire designed for construction equipment with reduced speed suitable for intermediate/high operations.
Provides stability, reduces maintenance time. Resistant to cuts and punctures.
It offers great load capacity.



#### APPLICATION:



TIRE SIZE	TRA CODE	RIM SIZE WIDTH	OVERALL DIAMETER		SECTION WIDTH		TREAD DEPTH		MAX LOAD CAPACITY							
									10 km/h				16 km/h			
									DRIVER		STEER		DRIVER		STEER	
(kg)	(lbs)	(kg)	(lbs)	(kg)	(lbs)	(kg)	(lbs)									
30x10-16 (10-16.5)	-	6.00	744	29.3	234	9.2	37	46.6	4.326	9.530	3.245	7.155	3.933	8.670	2.950	6.500
33x12-20 (12-16.5)	-	8.00	833	32.8	276	10.9	39	49.1	5.929	13.070	4.447	9.800	5.390	11.880	4.045	8.920



# GRIPMASTER

## SOLID MULTI-PURPOSE TIRES

### IND CARGO PREMIUM

#### MAIN FEATURES

Superelastic tire designed for construction equipment with reduced speed suitable for intermediate/high operations.

Provides stability, reduces maintenance time. Resistant to cuts and punctures.

It offers great load capacity.



#### APPLICATION:



TIRE SIZE	TRA CODE	RIM SIZE WIDHT (pol.)	OVERALL DIAMETER		SECTION WIDHT		TREAD DEPTH		MAX LOAD CAPACITY					
			(mm.)	(inch)	(mm.)	(inch)	(mm.)	(32nds)	LOAD		SPEED		WEIGHT	
			(mm.)	(inch)	(mm.)	(inch)	(mm.)	(32nds)	(kg.)	(lbs.)	(km/h)	(mph)	(kg.)	(lbs.)
33*6*11 (12-16.5)	-	12-16.5	820	32.3	273	10.8	48	60.5	4,075	8,980	10	5	134	295



# GRIPMASTER

## SOLID MULTI-PURPOSE TIRES

### IND CARGO PREMIUM

#### MAIN FEATURES

Superelastic tire designed for construction equipment with reduced speed suitable for intermediate/high operations.

Provides stability, reduces maintenance time. Resistant to cuts and punctures.

It offers great load capacity.



#### APPLICATION:



TIRE SIZE	TRA CODE	RIM SIZE WIDHT	OVERALL DIAMETER		SECTION WIDHT		TREAD DEPTH		MAX LOAD CAPACITY					
			(mm.)	(inch)	(mm.)	(inch)	(mm.)	(32nds)	LOAD		SPEED		WEIGHT	
									(kg.)	(lbs.)	(km/h)	(mph)	(kg.)	(lbs.)
31*6*10 (10-16.5)	-	10-16.5	756	29.8	255	10.0	53	66.8	3.415	7.530	10	5	107	235