



GRIPMASTER

SOLID CONSTRUCTION TIRES

IND CARGO PREMIUM

MAIN FEATURES

Construction equipment tires offer huge load capacity at low speeds.

Tire provides stability, resistance to cuts and punctures and reduces machine maintenance time.

The side holes serve for cushioning, in addition to cooling, preventing the tire from overheating.



APPLICATION:



TIRE SIZE	TRA CODE	RIM WIDTH SIZE	OVERALL DIAMETER		SECTION WIDTH		TREAD DEPTH		MAX LOAD CAPACITY						WEIGHT	
									10 km/h		16 km/h		26 km/h			
									(psi)	(Kpa)	(kg.)	(lbs)	(km/h)	(mph)	(kg.)	(lbs)
17.5-25	-	14.00	1.327	52.2	413	16.3	115	144.9	13.000 / 10.500	28.660 / 23.149	11.000 / 8.000	24.251 / 17.637	8.500 / 7.000	18.739 / 15.432	454	1.001
20.5-25	-	17.00	1.350	53.1	485	19.1	150	189.0	15.000 / 11.000	33.069 / 24.251	13.000 / 8.560	28.660 / 18.872	10.000 / 7.500	22.046 / 16.535	743	1.638
23.5-25	-	19.50	1.570	61.8	543	21.4	142	178.9	19.500 / 14.500	42.990 / 31.967	17.000 / 13.000	37.479 / 28.660	13.500 / 11.500	29.762 / 25.353	926	2.042
26.5-25	-	22.00	1.680	66.1	620	24.4	123	155.0	39.300 / 31.400	86.640 / 69.225	-	-	35.400 / 26.600	78.040 / 58.640	1.300	2.866