

BIAS AGRICULTURAL TIRES

G-AGRI 530WD

MAIN FEATURES

Tire for agricultural tractors and backhoe used on directional wheels

Provides excellent handling, self-cleaning and lateral stability.

Precision in the direction avoiding skidding.

Special rubber compound that provides greater performance to the tire.







	TRA CODE	PLY RATING	TYPE	RIM SIZE WIDTH	OVERALL DIAMETER		SECTION WIDHT		ROLLING CIRCUM ± 2.5%		TREAD DEPTH		MAX LOAD CAPACITY					
TIRE SIZE													LOAD		INFLATION PRESSURE		SPEED	
				(pol.)	(mm.)	(inch.)	(mm.)	(inch.)	(mm.)	(inch.)	(mm.)	(32nds)	(kg.)	(lbs)	(psi)	(Kpa)	(km/h)	(mph)
10.5/65-16	F-3	10	TL	9.00	755	29.7	274	10.8	2.210	87.0	8	10	1.550	3.420	75	520	40	25
10.5/65-16	F-3	14	TL	9.00	755	29.7	274	10.8	2.210	87.0	8	10	1.900	4.180	104	715	40	25
10.5/65-16	F-3	16	TL	9.00	755	29.7	274	10.8	2.210	87.0	8	10	2.070	4.560	107	740	40	25