

BIAS AGRICULTURAL TIRES

G-AGRI 730WD

MAIN FEATURES

Tires for modern agriculture.

Excellent performance in transport and agricultural application.

Low section implement tires that offer high load capacity with minimal soil compaction.



APPLICATION:



TIRE SIZE	TRA CODE	PLY RATING	TYPE	RIM SIZE WIDTH		OVERALL DIAMETER		SECTION WIDTH		ROLLING CIRCUM ± 2.5%		TREAD DEPTH		MAX LOAD CAPACITY					
				(pol.)	(mm.)	(inch.)	(mm.)	(inch.)	(mm.)	(inch.)	(mm.)	(32nds)	LOAD		INFLATION PRESSURE		SPEED		
													(kg.)	(lbs)	(psi)	(Kpa)	(km/h)	(mph)	
10.0/80-12	I-3	10	TL	9.00	710	28.0	264	10.4	2.083	82.0	8	9	1.420	3.124	77	530	40	25	
10.0/75-15.3	I-3	10	TL	9.00	760	29.9	264	10.4	2.235	88.0	8	10	1.550	3.410	74	510	40	25	
10.0/75-15.3	I-3	12	TL	9.00	760	29.9	264	10.4	2.235	88.0	8	10	1.700	3.750	91	627	40	25	
10.0/75-15.3	I-3	14	TL	9.00	760	29.9	264	10.4	2.235	88.0	8	10	1.900	4.180	101	696	40	25	
10.0/75-15.3	I-3	16	TL	9.00	760	29.9	264	10.4	2.235	88.0	8	10	2.120	4.670	104	717	40	25	
10.0/75-15.3	I-3	18	TL	9.00	760	29.9	264	10.4	2.235	88.0	8	10	2.360	5.192	101	696	40	25	
10.0/75-15.3	I-3	22	TL	9.00	760	29.9	264	10.4	2.235	88.0	8	10	2.750	6.050	108	744	40	25	
11.5/80-15.3	I-3	12	TL	9.00	845	33.2	290	11.4	2.464	97.0	9	11	2.180	4.800	79	544	40	25	
11.5/80-15.3	I-3	14	TL	9.00	845	33.2	290	11.4	2.464	97.0	9	11	2.430	5.346	92	634	40	25	
11.5/80-15.3	I-3	16	TL	9.00	845	33.2	290	11.4	2.464	97.0	9	11	2.575	5.675	101	696	40	25	
11.5/80-15.3	I-3	18	TL	9.00	845	33.2	290	11.4	2.464	97.0	9	11	2.900	6.375	111	765	40	25	
11.5/80-15.3	I-3	22	TL	9.00	845	33.2	290	11.4	2.464	97.0	9	11	3.250	7.150	112	772	40	25	
12.5/80-15.3	I-3	14	TL	9.00	890	35.0	315	12.4	2.591	102.0	9	11	2.650	5.825	84	579	40	25	
12.5/80-15.3	I-3	16	TL	9.00	890	35.0	315	12.4	2.591	102.0	9	11	2.800	6.160	92	634	40	25	
13.0/55-16	I-3	14	TL	11.00	770	30.3	336	13.2	2.261	89.0	9	11	2.240	4.928	84	579	40	25	
13.0/70-16	I-3	10	TL	11.00	770	30.3	336	13.2	2.261	89.0	9	11	2.060	4.532	70	482	40	25	
13.0/70-16	I-3	14	TL	11.00	770	30.3	336	13.2	2.261	89.0	9	11	2.240	4.928	82	565	40	25	
13.0/75-16	I-3	10	TL	11.00	900	35.4	340	13.4	2.718	107.0	9	11	2.360	5.192	60	413	40	25	
13.0/75-16	I-3	14	TL	11.00	900	35.4	340	13.4	2.718	107.0	9	11	2.841	6.250	82	565	40	25	
14.0/65-16	I-3	14	TL	11.00	871	34.3	353	13.9	2.540	100.0	9	11	2.900	6.380	80	551	40	25	
13.0/65-18	I-3	16	TL	11.00	890	35.0	336	13.2	2.616	103.0	9	11	2.800	6.160	95	655	40	25	
13.0/65-18	I-3	18	TL	11.00	890	35.0	336	13.2	2.616	103.0	9	11	3.050	6.720	101	696	40	25	
340/70-18	I-3	16	TL	11.00	902	35.5	342	13.5	2.642	104.0	9	11	3.650	8.030	101	696	40	25	