



GRIPMASTER

BIAS CONSTRUCTION TIRES

G-EARTH 1130GD

MAIN FEATURES

Tire features excellent traction

Design and tread compound provide excellent cut resistance

Extended tire life because of greater tread depth



APPLICATION:



TIRE SIZE	TRA CODE	PLY RATING	TYPE	RIM SIZE WIDTH	OVERALL DIAMETER		SECTION WIDTH		TREAD DEPTH		MAX LOAD CAPACITY					
											LOAD		INFLATION PRESSURE		SPEED	
											(kg.)	(lbs)	(psi)	(Kpa)	(km/h)	(mph)
16/70-20	E3/L3	14	TT	13.00	1.075	42.3	410	16.1	22	27.7	2.900	6.395	50	345	50	30
15.5-25	E3/L3	12	TT/TL	12.00	1.275	50.2	395	15.6	26.5	33.4	5.600/3.250	12.000/7.150	58/36	400/250	10/50	5/30
15.5-25	E3/L3	16	TT/TL	12.00	1.275	50.2	395	15.6	26.5	33.4	6.500/3.750	8250/14330	76/47	525/325	10/50	5/30
17.5-25	E3/L3	12	TT/TL	14.00	1.350	53.1	445	17.5	31.5	39.7	6.150/3.650	13.600/8.050	51/33	350/225	10/50	5/30
17.5-25	E3/L3	14	TT	14.00	1.350	53.1	445	17.5	31.5	39.7	6.700/4.125	14.800/9.090	65/40	450/275	10/50	5/30
17.5-25	E3/L3	16	TT/TL	14.00	1.350	53.1	445	17.5	31.5	39.7	7.300/4.250	16.100/9.350	69/44	475/300	10/50	5/30
17.5-25	E3/L3	20	TT/TL	14.00	1.350	53.1	445	17.5	31.5	39.7	8.250/5.000	18.200/11.000	83/58	575/400	10/50	5/30
17.5-25	E3/L3	24	TL	14.00	1.350	53.1	445	17.5	31.5	39.7	9.250/5.600	20.400/12.300	101/69	695/475	10/50	5/30
17.5-25	E3/L3	32	TL	14.00	1.350	53.1	445	17.5	31.5	39.7	10.900	24.000	134	920	10	5
17.5-25	E3/L3	40	TL	14.00	1.350	53.1	445	17.5	31.5	39.7	12.500	27.600	170	1.170	10	5
20.5-25	E3/L3	12	TT/TL	17.00	1.490	58.7	520	20.5	32.0	40.3	6.700/4.500	14.800/9.900	36/29	250/200	10/50	5/30
20.5-25	E3/L3	16	TT/TL	17.00	1.490	58.7	520	20.5	34.5	40.3	8.250/5.450	18.200/12.000	51/40	350/275	10/50	5/30
20.5-25	E3/L3	18	TT	17.00	1.490	58.7	520	20.5	34.5	40.3	8.920/5.730	19.700/12.600	58/44	400/300	10/50	5/30
20.5-25	E3/L3	20	TT/TL	17.00	1.490	58.7	520	20.5	34.5	40.3	9.500/6.000	20.900/13.200	65/46	450/325	10/50	5/30
20.5-25	E3/L3	24	TT/TL	17.00	1.490	58.7	520	20.5	34.5	40.3	1.0300/6.700	22.700/14.800	76/58	525/400	10/50	5/30
20.5-25	E3/L3	28	TL	17.00	1.490	58.7	520	20.5	34.5	40.3	11500/7500	25353/15530	91/69	625/475	10/50	5/30
23.5-25	E3/L3	16	TT/TL	19.50	1.615	63.6	595	23.4	38	47.9	9.500/6.150	20.900/8.050	44/33	300/225	10/50	5/30
23.5-25	E3/L3	18	TT	19.50	1.615	63.6	595	23.4	38	47.9	10.300/6.500	22.700/14.330	51/36	350/250	10/50	5/30
23.5-25	E3/L3	20	TT/TL	19.50	1.615	63.6	595	23.4	38	47.9	10.900/7.300	24.000/16.100	54/44	375/300	10/50	5/30
23.5-25	E3/L3	24	TT/TL	19.50	1.615	63.6	595	23.4	38	47.9	12.500/8.000	27.600/17.600	69/51	475/350	10/50	5/30
23.5-25	E3/L3	32	TT	19.50	1.615	63.6	595	23.4	38	47.9	14500/9250	20.400/31.950	91/65	450/625	10/50	5/30
23.5-25	E3/L3	28	TL	19.50	1.615	63.6	595	23.4	38	47.9	13.600/8.750	30.000/19.300	80/58	550/400	10/50	5/30
26.5-25	E3/L3	20	TL	22.00	1.750	68.9	675	26.6	38	47.9	13.200/8.250	29.100/18.200	51/36	350/250	10/50	5/30
26.5-25	E3/L3	24	TL	22.00	1.750	68.9	675	26.6	38	47.9	14.000/9.250	30.900/20.400	58/44	400/300	10/50	5/30
26.5-25	E3/L3	28	TL	22.00	1.750	68.9	675	26.6	38	47.9	15.500/10.000	34.200/22.000	69/51	475/350	10/50	5/30
26.5-25	E3/L3	32	TL	22.00	1.750	68.9	675	26.6	38	47.9	17.000/11.200	24.700/37.500	80/62	550/425	10/50	5/30
26.5-25	E3/L3	44	TL	22.00	1.750	68.9	675	26.6	38	47.9	20.800	45.800	112	775	10	5
29.5-25	E3/L3	22	TL	25.00	1.875	73.8	750	29.5	43	54.2	15.000/10.000	34.200/22.000	46/36	325/250	10/50	5/30
29.5-25	E3/L3	28	TL	25.00	1.875	73.8	750	29.5	43	54.2	17.500/11.500	38.600/25.400	62/46	425/625	10/50	5/30
29.5-25	E3/L3	34	TL	25.00	1.875	73.8	750	29.5	43	54.2	20.000/12.950	44.100/28.500	76/58	525/400	10/50	5/30
33.25-29	E3/L3	32	TL	27.00	2.090	82.3	845	33.3	42.5	53.5	23.600/15.000	52.000/33.100	65/46	450/325	10/50	5/30
33.25-29	E3/L3	38	TL	27.00	2.090	82.3	845	33.3	42.5	53.5	25.750/17.000	56800/37.500	76/58	525/400	10/50	5/30