



GRIPMASTER

BIAS CONSTRUCTION TIRES

G-EARTH 642WD

MAIN FEATURES

Deep grooves with robust design provide performance and durability.

Reinforced sidewall resistant to cuts and cracks.



APPLICATION:



| TIRE SIZE | TRA CODE | PLY RATING | TYPE | RIM SIZE WIDTH | OVERALL DIAMETER | | SECTION WIDTH | | ROLLING CIRCUM ± 2.5% | | TREAD DEPTH | | MAX LOAD CAPACITY | | | | | |
|------------|----------|------------|------|----------------|------------------|---------|---------------|---------|-----------------------|---------|-------------|---------|-------------------|-------|--------------------|-------|--------|-------|
| | | | | | (mm.) | (inch.) | (mm.) | (inch.) | (mm.) | (inch.) | (mm.) | (32nds) | LOAD | | INFLATION PRESSURE | | SPEED | |
| | | | | (pol.) | (mm.) | (inch.) | (mm.) | (inch.) | (mm.) | (inch.) | (mm.) | (32nds) | (kg.) | (lbs) | (psi) | (Kpa) | (km/h) | (mph) |
| 33x12.5-15 | R-4 | 12 | TL | 10.00 | 851 | 33.5 | 318 | 12.5 | 2.489 | 98.0 | 20 | 25 | 2.575 | 5.675 | 54 | 372 | 40 | 25 |
| 12.5/70-16 | R-4 | 10 | TL | 10.00 | 853 | 33.6 | 315 | 12.4 | 2.590 | 102.0 | 20 | 25 | 1.380 | 3.040 | 30 | 207 | 40 | 25 |
| 12.5/70-16 | R-4 | 14 | TL | 10.00 | 853 | 33.6 | 315 | 12.4 | 2.590 | 102.0 | 20 | 25 | 1.650 | 3.630 | 38 | 262 | 40 | 25 |
| 12.5/70-16 | R-4 | 16 | TL | 10.00 | 853 | 33.6 | 315 | 12.4 | 2.590 | 102.0 | 20 | 25 | 1.900 | 4.190 | 42 | 290 | 40 | 25 |
| 15.5/60-18 | R-4 | 12 | TL | 13.00 | 950 | 37.4 | 401 | 15.8 | 2.870 | 113.0 | 22 | 28 | 2.240 | 4.940 | 35 | 241 | 40 | 25 |
| 15.5/60-18 | R-4 | 14 | TL | 13.00 | 950 | 37.4 | 401 | 15.8 | 2.870 | 113.0 | 22 | 28 | 2.400 | 5.280 | 38 | 262 | 40 | 25 |
| 15.5/70-18 | R-4 | 14 | TL | 13.00 | 1.031 | 40.6 | 401 | 15.8 | 3.099 | 122.0 | 22 | 28 | 2.650 | 5.840 | 38 | 262 | 40 | 25 |
| 17.5/65-20 | R-4 | 14 | TL | 14.00 | 1.090 | 42.9 | 450 | 17.7 | 3.302 | 130.0 | 25 | 31 | 3.200 | 7.040 | 35 | 241 | 40 | 25 |
| 16.9-24 | R-4 | 12 | TL | 15.00 | 1.303 | 51.3 | 450 | 17.7 | 3.785 | 149.0 | 30 | 38 | 3.250 | 7.150 | 38 | 262 | 40 | 25 |
| 17.5L-24 | R-4 | 12 | TL | 15.00 | 1.270 | 50.0 | 452 | 17.8 | 3.683 | 145.0 | 28 | 35 | 3.159 | 6.950 | 38 | 262 | 40 | 25 |
| 17.5L-24 | R-4 | 16 | TL | 15.00 | 1.270 | 50.0 | 452 | 17.8 | 3.683 | 145.0 | 28 | 35 | 3.790 | 8.338 | 48 | 331 | 40 | 25 |