

SOLID INDUSTRIAL TIRES

G-IND 1000HS

MAIN FEATURES

Tires for industrial use vehicles. Suitable for intermediate operations from 2 to 3 turns.

Tread with excellent puncture resistance and deep blocks produced with high performance compound.

Exclusive design provides great stability, rolling resistance and reduced vibration.





TIRE SIZE	RIM SIZE	OVERALL DIAMETER		SECTION WIDHT		TREAD DEPTH		MAX LOAD CAPACITY COUNTERBALANCED FORKLIFT								OTHER EQUIPMENTS	
	WIDHT							10 km/h				16 km/h				EQUITIVE ITTS	
								DRIVER		STEER		DRIVER		STEER		10 km/h	
	(po l)	(mm)	(inch.)	(mm)	(inch.)	(mm)	(32nds.)	(kg)	(lbs.)	(kg)	(lbs.)	(kg)	(l bs.)	(kg)	(lbs.)	TO KIII/II	
10.00-20	8.00	1.073	42.0	278	11.0	40	50	7.300	16.100	6.085	13.420	6.670	14.700	5.560	12.260	5.630	12.400
12.00-20	8.00	1.180	46.0	310	12.0	45	57	8.640	19.050	7.200	15.875	7.885	17.385	6.570	14.490	6.650	14.660