



GRIPMASTER

BIAS MULTI-PURPOSE TIRES

G-MPT 250WD

MAIN FEATURES

Designed for wheel loaders, special traction and extra deep tread.

Ideal for high and medium operation with high impact, used at low speeds.

Special rubber compound that provides greater performance to the tire.



APPLICATION:



TYRE SIZE	TRA CODE	PLY RATING	TYPE	RIM SIZE WIDHT	OVERALL DIAMETER		SECTION WIDHT		ROLLING CIRCUM ± 2.5%		TREAD DEPHT		MAX LOAD CAPACITY						
					(pol.)	(mm.)	(inch.)	(mm.)	(inch.)	(mm.)	(inch.)	(mm.)	(32nds)	LOAD		INFLATION PRESSURE		SPEED	
														(kg.)	(lbs)	(psi)	(Kpa)	(km/h)	(mph)
23x8.50-12	L-5	8	TL	7.00	584	23.0	216	8.5	1.727	68.0	22	27.5	690	1.518	50	345	25	16	
27x8.50-15	L-5	10	TL	7.00	676	26.6	218	8.6	2.006	79.0	22	27.5	1.000	2.200	61	420	25	16	
11L-16	L-5	12	TL	8.00	820	32.3	280	11.0	2.438	96.0	22	27.5	1.150	2.756	64	440	40	25	
11L-16	L-5	14	TL	8.00	820	32.3	280	11.0	2.438	96.0	22	27.5	1.375	3.025	70	485	40	25	
10-16.5	L-5	12	TL	8.25	798	31.4	259	10.2	2.397	94.4	43	54.0	2.180	4.796	64	440	25	16	
10-16.5	L-5	14	TL	8.25	798	31.4	259	10.2	2.397	94.4	43	54.0	2.360	5.190	68	470	25	16	
12-16.5	L-5	14	TL	9.75	838	33.0	307	12.1	2.515	99.0	44	55.0	2.765	6.083	70	485	25	16	
12-16.5	L-5	16	TL	9.75	838	33.0	307	12.1	2.515	99.0	44	55.0	3.000	6.600	74	510	25	16	
14-17.5	L-5	14	TL	10.5	935	36.8	358	14.1	2.743	108.0	44	55.0	3.900	8.580	78	540	25	16	
12.5/80-18	L-5	14	TL	9.00	975	38.4	305	12.0	2.896	114.0	33	44.0	2.430	5.345	50	345	40	25	
12.5/80-18	L-5	16	TL	9.00	975	38.4	305	12.0	2.896	114.0	33	44.0	2.650	5.830	55	380	40	25	
19.5L-24	L-5	16	TL	17.00	1.298	51.1	490	19.3	3.835	151.0	38	48.0	4.135	9.097	44	300	40	25	
18.4-26	L-5	12	TL	16.00	1.425	56.1	475	18.7	4.191	165.0	28	38.0	4.000	8.800	36	250	40	25	
16.9-28	L-5	12	TL	15.00	1.410	55.5	440	17.3	4.140	163.0	30	38.0	3.550	7.810	28	195	40	25	