

BIAS MULTI-PURPOSE TIRES

G-MPT 920WD

MAIN FEATURES

Tire with reinforced sidewall and compounds of greater resistance to cuts and punctures.

Design provides excellent traction, designed for different soils, mixed and intermediate operations.

Greater rubber depth designed for better performance and tire life.



APPLICATION:



TYRE SIZE	TRA CODE	PLY RATING	TYPE	RIM SIZE WIDHT	OVERALL DIAMETER		SECTION WIDHT		ROLLING CIRCUM ± 2.5%		TREAD DEPHT		MAX LOAD CAPACITY					
													LOAD		INFLATION PRESSURE		SPEED	
				(pol.)	(mm.)	(inch.)	(mm.)	(inch.)	(mm.)	(inch.)	(mm.)	(32nds)	(kg.)	(lbs)	(psi)	(KPa)	(km/h)	(mph)
10-16.5	SKS-2	8	TL	8.25	795	31.3	268	10.5	2.286	90.0	16	20	1.370	3.014	60	414	25	16
10-16.5	SKS-2	10	TL	8.25	795	31.3	268	10.5	2.286	90.0	16	20	1.560	3.432	75	517	25	16
12-16.5	SKS-2	10	TL	9.75	853	33.6	325	12.8	2.438	96.0	20	25	1.860	4.092	64	441	25	16
12-16.5	SKS-2	12	TL	9.75	853	33.6	325	12.8	2.438	96.0	20	25	2.060	4.532	74	510	25	16