

BIAS INDUSTRIAL TIRES

G-PREMIUM IND 1000HD (DEEP TREAD PATTERN 1000)

MAIN FEATURES

Tires tested in high intensity operations, ensuring low wear, bringing great results.

Increased stability of the equipment and comfort for the operator, in addition to traction due to the tread being robust and having a uniform protection design.

Double reinforced bead for operations with greater twist and weight, preventing air leakage through the wheel, even in more severe operations.

Reinforced sidewall, providing excellent resistance to cuts and damage.



APPLICATION:



TIRE SIZE	PLY RATING	TYPE	RIM SIZE WIDTH	OVERALL DIAMETER		SECTION WIDTH		TREAD DEPTH		MAX LOAD CAPACITY		INFLATION PRESSURE		SPEED	
			(inch.)	(mm)	(inch.)	(mm)	(inch.)	(mm)	(32nds)	(kg)	(lbs)	(psi)	(Kpa)	(km/h)	(mph)
5.00-8	10	TT	3.50	470	18.5	142	5.6	23	29	1.150	2.530	145	1.000	25	16
6.00-9	12	TT	4.00F	555	21.8	168	6.6	26	33	1.675	3.695	149	1.030	25	16
6.50-10	12	TT	5.00F	599	23.6	185	7.3	31	39	1.895	4.180	145	1.000	25	16
7.00-12	14	TT	5.00S	680	26.8	200	7.9	33.5	42	2.590	5.710	142	1.000	25	16
8.25-15	16	TT	6.50	851	33.5	246	9.7	33.5	42	4.050	8.930	134	925	25	16
28x9-15	16	TT	7.00	713	28.1	224	8.8	28	35	3.115	6.870	145	1.000	25	16