



GRIPMASTER

UNDERGROUND RADIAL MINING TIRES

G-PREMIUM MINE 250SXR (L-5S)

MAIN FEATURES
Radial OTR with extra deep tread and sturdy shoulders
Reinforced sidewall designed for impact resistance.
Smooth tread offers protection and prevents rubber tearing in severe operations.



TIRE SIZE	TRA CODE	PLY RATING	TYPE	RIM SIZE WIDTH	OVERALL DIAMETER		SECTION WIDTH		TREAD DEPTH		MAX LOAD CAPACITY					
					(mm.)	(inch.)	(mm.)	(inch.)	(mm.)	(32nds)	LOAD		INFLATION PRESSURE		SPEED	
											(pol.)	(kg.)	(lbs.)	(psi)	(Kpa)	(km/h)
23.5R25	L-5S	★★	TL	19.50/2.5	1.673	66	597	24	78	98	14.500	31.970	94	650	10	5
26.5R25	L-5S	★★	TL	22.00/3.0	1.798	71	673	26	87	110	18.500	40.785	94	650	10	5
29.5R25	L-5S	★★	TL	25.00/3.5	1.921	76	750	30	95	120	22.400	49.380	94	650	10	5
29.5R29	L-5S	★★	TL	25.00/3.5	2.023	80	750	30	95	120	23.600	52.030	94	650	10	5