



GRIPMASTER

RADIAL CONSTRUCTION TIRES

G-PRO 390

MAIN FEATURES

Structure and special rubber compound that provides excellent performance and high resistance.

Tire with wide tread and reinforced sidewall ensure greater protection against cuts and punctures

Traction tire designed for high intensity mixed operations, featuring the "S" design on the tread in order to avoid dirt accumulation.



APPLICATION:



TIRE SIZE	TRA CODE	PLY RATING	COMPOUND	TYPE	RIM SIZE WIDHT	OVERALL DIAMETER		SECTION WIDHT		TREAD DEPTH		MAX LOAD CAPACITY					
						(mm.)	(inch.)	(mm.)	(inch.)	(mm.)	(32nds)	LOAD		INFLATION PRESSURE		SPEED	
												(kg.)	(lbs.)	(psi)	(Kpa)	(km/h)	(mph)
17.5R25	E3/L3	***	2S	TL	14.00/1.5	1.340	52.8	440	17.3	29	37	5.450 / 8.500	12.000 / 18.700	76/94	525/650	50/10	30/5
20.5R25	E3/L3	**/*	2S	TL	17.00	1.470	57.9	508	20	33	42	7.300 / 9.500	16.100 / 20.950	76/73	525/500	50/10	30/5
23.5R25	E3/L3	**/*	2S	TL	19.50	1.600	63	595	23.4	36	45	9.250 / 12.150	20.400 / 26.800	76/73	525/500	50/10	30/5
26.5R25	E3/L3	**/*	2S	TL	22.00	1.740	68.5	660	26	38	48	11.500 / 15.000	25.350 / 33.100	76/73	525/500	50/10	30/5
29.5R25	E3/L3	**/*	2S	TL	25.00	1.850	72.8	745	29.3	43	54	14.000 / 18.000	30.900 / 39.700	76/73	525/500	50/10	30/5