

## RADIAL MINING TIRES

### G-PRO 580

#### MAIN FEATURES

Directional shaped tread that ensures excellent traction and grip on mixed terrain.

Reinforced structure, extra deep grooves and special compound, guarantee greater durability and hours worked.

Optimized shoulder design and special lateral compound provide excellent performance even in severe operations.



TIRE SIZE	TRA CODE	PLY RATING	TYPE	RIM SIZE WIDHT	OVERALL DIAMETER		SECTION WIDHT		TREAD DEPTH		MAX LOAD CAPACITY					
					(mm.)	(inch.)	(mm.)	(inch.)	(mm.)	(32nds)	LOAD		INFLATION PRESSURE		SPEED	
											(kg.)	(lbs.)	(psi)	(Kpa)	(km/h)	(mph)
20.5R25	L-5	**	TL	17.00	1.530	60.2	525	20.7	72	90.7	11.500	25.350	94	650	10	5
23.5R25	L-5	**	TL	19.50	1.650	65.0	605	23.8	77	97	14.500	31.970	94	650	10	5
26.5R25	L-5	**	TL	22.00	1.775	69.9	675	26.6	85	107.1	18.500	40.785	94	650	10	5
29.5R25	L-5	**	TL	25.00	1.880	74.0	750	29.5	98	123.5	22.400	49.380	94	650	10	5