

BIAS AGRICULTURAL TIRES

G-PRO AGRI 520GD

MAIN FEATURES

Tire suitable for front wheels of agricultural tractors

Tire has excellent lateral slip resistance and low rolling resistance providing fuel savings.

Tire has cut resistance.



APPLICATION:

TIRE SIZE	TRA CODE	PLY RATING	TYPE	RIM SIZE WIDTH	OVERALL DIAMETER			SECTION WIDTH		TREAD DEPTH		MAX LOAD CAPACITY					
					(pol.)	(mm.)	(inch.)	(mm.)	(inch.)	(mm.)	(32nds)	LOAD		INFLATION PRESSURE		SPEED	
												(kg.)	(lbs)	(psi)	(Kpa)	(km/h)	(mph)
4.00-12	F-2	4	TL	3.00	539	21.2	112	4.4	12	15.1	225	495	52	360	40	25	
4.00-15	F-2	4	TL	12.00	616	24.2	112	4.4	12	15.1	265	584.2	52	358.5	40	25	
5.00-15	F-2	6	TT	3.00	664	26.1	130	5.1	13	16.4	465	1.025	61	420	40	25	
11L-15	F-2	8	TT	8.00	813	32	279	11	27.5	34.6	950	2.090	44	300	40	25	
5.50-16	F-2	6	TT	4.00	713	28.1	150	5.9	13	16.4	475	1.050	56	390	40	25	
6.00-16	F-2	6	TT	4.00	739	29.1	159	6.3	15	18.9	515	1.140	52	360	40	25	
6.50-16	F-2	8	TL	4.50	761	30	173	6.8	18	22.7	735	1.620	61	420	40	25	
9.00-16	F-2	10	TL	6.00	860	33.9	235	9.3	22	27.7	1.120	2.470	56	390	40	25	
10.00-16	F-2	8	TL	8.00	894	35.2	274	10.8	26	32.8	1.060	2.340	44	300	40	25	
11.00-16	F-2	8	TL	10.00	967	38.1	315	12.4	24	30.2	1.180	2.600	40	280	40	25	
7.50-18	F-2	6	TL	5.50	859	33.8	203	8	21	26.5	730	1.610	44	300	40	25	
4.00-19	F-2	4	TL	3.00	717	28.2	112	4.4	12	15.1	325	715	52	360	40	25	
6.50-20	F-2	8	TL	5.00	860	33.9	180	7.1	18	22.7	865	1.905	61	420	30	20	
7.50-20	F-2	8	TT	5.50	909	35.8	203	8	21	26.5	900	1.985	56	390	40	25	