



GRIPMASTER

BIAS CONSTRUCTION TIRES

G-PRO EARTH 410GD

MAIN FEATURES

Designed to provide excellent performance for compaction operations.

Tread with excellent resistance to high temperatures.



APPLICATION:

TIRE SIZE	TRA CODE	PLY RATING	TYPE	RIM SIZE WIDTH	OVERALL DIAMETER		SECTION WIDTH		TREAD DEPTH		MAX LOAD CAPACITY					
											LOAD		INFLATION PRESSURE		SPEED	
											(pol.)	(mm.)	(inch.)	(mm.)	(inch.)	(mm.)
9.5/65-15	C-1	6	TT	7.00	673	26.5	235	9.3	12	15.1	1.315	2.900	47	325	10	5
7.50-15	C-1	14	TT	6.00	785	30.9	215	8.5	20	25.2	2.900	6.400	127	875	10	5
7.50-16	C-1	14	TT	6.00G	810	31.9	215	8.5	18	22.7	3.075	6.780	134	925	10	5
10.5/80-16	C-1	6	TT	8.00	812	32.0	263	10.4	12	15.1	1.875	4.135	44	300	10	5
12.00-16	C-1	12	TT	8.50	1.020	40.2	315	12.4	26	32.8	4.625	10.200	80	550	10	5
9.00-20	C-1	12	TT	7.00	1.015	40.0	255	10.0	20	25.2	4.000	8.800	91	625	10	5
9.00-20	C-1	14	TT	7.00	1.015	40.0	255	10.0	20	25.2	4.375	9.650	105	725	10	5
9.00-20	C-1	16	TT	7.00	1.015	40.0	255	10.0	20	25.2	4.750	10.500	120	825	10	5
11.00-20	C-1	16	TT	8.00	1.080	42.5	290	11.4	22	27.7	5.450	12.000	105	725	10	5
11.00-20	C-1	18	TT	8.00	1.080	42.5	290	11.4	22	27.7	5.800	12.800	120	825	10	5
11.00-20	C-1	24	TT	8.00	1.080	42.5	290	11.4	22	27.7	7.100	15.655	163	1.125	10	5
12.00-20	C-1	16	TT	8.50	1.120	44.1	315	12.4	26	32.8	6.000	13.230	98	675	10	5
12.00-20	C-1	24	TT	8.50	1.120	44.1	315	12.4	26	32.8	7.500	16.535	149	1.025	10	5
13/80-20	C-1	16	TT	8.50	1.060	41.7	320	12.6	20	25.2	5.450	12.015	116	800	10	5
14/70-20	C-1	14	TT	11.00TG	980	38.6	355	14.0	28	35.3	4.270	9.400	73	500	10	5