

## SOLID INDUSTRIAL TIRES

## G-PRO IND 1000GS

## MAIN FEATURES

Tire for application in heavy operations of forklifts and other industrial equipment.

Flat tread and special rubber compound provide extended tire life as well as increased resistance against damage.

Manufactured in state-of-the-art machinery that guarantees consistency of compounds, uniformity in dimensions and high performance.



APPLICATION:



TIRE SIZE	RIM SIZE WIDHT							MAX LOAD CAPACITY									
		OVERALL DIAMETER		SECTION WIDHT	TREAD DEPTH	COUNTERBALANCED FORKLIFT				OTHER INDUSTRIAL VEHICLE							
		DIAIV	IEIEK	WIDHI	DEPIN	PIN		25 k	cm/h		6km/h		10km/h		25km/h		
							DRIVER		STEER		(kg)	(lbs.)	(kg)	(lbs.)	(kg)	(lbs.)	
	(pol)	(mm)	(inch.)	(mm)	(inch.)	(mm)	(32nds.)	(kg)	(lbs.)	(kg)	(lbs.)	( 8,	(====,	\ <i>\-</i>		(8/	(
10.00-20	8.00	1.012	39.8	249	9.8	32	40.3	6.000	13.225	5.000	11.020	6.500	14.330	5.450	12.010	5.000	11.020